

# ELIMINATOR™-GAPMASTER™ II 610 Series Dock Shelter

## PART 1 - GENERAL

Page 1 of 2

- 1.1 CONDITIONS SPECIFIED ELSEWHERE: Section 010000 - General Requirements.
- 1.2 SUBMIT SHOP DRAWINGS showing overall dimensions (width, height).
- 1.3 SUBMIT 3 copies of manufacturer's owner's manual.
- 1.4 WARRANTY: Proposals submitted without the following written warranties will be considered non-responsive.
  - 1.4.1 Shelter manufacturer shall provide with his bid a written minimum 1-year parts and labor warranty, detailed specification sheet with sizes, projection, range of trucks to be serviced, and any other information necessary for proper installation and operation of the unit.
  - 1.4.2 Shelter parts not covered under the warranty shall include: NONE.
  - 1.4.3 In addition to all other warranties, the manufacturer shall warrant that the equipment will perform in a manner satisfactory to the Owner for a period of 12 months after date of installation. If Owner is not then satisfied with the performance of the equipment, the Owner may notify the manufacturer, and the manufacturer shall remove the equipment and refund the equipment purchase price to the Owner. This warranty shall be provided by the manufacturer in writing at time of bid.

## PART 2 - PRODUCTS

- 2.1 Shelter shall be manufactured by **Rite-Hite** or an approved substitute. Shelter shall be sized by manufacturer to meet specific application requirements.
- 2.2 Shelter shall be \_\_\_\_\_' \_\_\_\_\_" overall unit width x \_\_\_\_\_' \_\_\_\_\_" unit height off grade x \_\_\_\_\_" projection.
  - 2.2.1 Range of truck heights to be serviced shall be from \_\_\_\_\_' \_\_\_\_\_" to \_\_\_\_\_' \_\_\_\_\_".
- 2.3 Side curtains shall provide full access to trailer and shall be removable. Removal shall require no tools.
  - 2.3.1 Side curtains shall be attached with Touch-N-Hold fastening and furnished with stay stiffeners in fabric panels.
  - 2.3.2 Side curtains shall have HMWPE hooks on edges to seal hinged door trailers.

- 2.4 Head curtain shall be constructed as a canopy style header with a pivoting steel tube frame, an integrated gutter and have overlapping wear pleats on ends of head curtain face.
  - 2.4.1 Head curtain shall be include stay stiffeners in curtain face to seal top of trailer.
  - 2.4.2 Height of head curtain shall be 6” below height of normal lowest truck to be serviced.
- 2.5 Side frame shall be constructed with HMWPE sheets, foam and be impactable.
  - 2.5.1 Side frame fabric shall be lightweight to match curtain fabric.
- 2.6 Side curtain and head curtain fabric shall be \_\_\_\_\_.  
Optional fabrics are available.
- 2.7 Collapsible bottom pads shall seal the gap between the side curtain and the building wall.

**PART 3 - EXECUTION**

- 3.1 **INSTALLER** shall examine the substrate and conditions under which shelter/seal is to be installed and notify the A/E and Contractor in writing of any conditions detrimental to the proper and timely completion of the work. Do not proceed with the work until unsatisfactory conditions have been corrected in a manner acceptable to the installer.
- 3.2 **SHELTER MANUFACTURER’S REPRESENTATIVE** shall install shelter/seal in accordance with approved shop drawings and manufacturer’s recommendations.
- 3.3 **AFTER INSTALLATION** is completed, a representative of the manufacturer shall examine the installation and require that all adjustments necessary to assure proper operation of shelter/seal has been made. Before acceptance, an inspection shall be conducted in the presence of the Owner’s representative to guarantee that the shelter/seal operates properly in every respect.